

FRICKE

Maszyny Rolnicze

FRICKE Maszyny Rolnicze Sp. z o.o. Mragowo
Ul. Przemysłowa 6
11-700 Mragowo
Tel: +48 783 222 777
Fax:

Grimme SE 260 [41101490]

Year of manufacture: 2022

Date: 25.11.2024

Design:

Potato Technology

Category:

Potato harvester

682.100,⁰⁰ zł

plus VAT 23% (838.983,⁰⁰ zł Gross)



Equipment

State

Used

Description:

- 2-row-combine-harvester-model-se-260-demo-demonstration-machine-equipment-specifications-ball-hitch-80-mm-relay-shaft-drive-540-rpm-row-spacing-80-cm-cutting-width-620-mm-separately-adjustable-center-blade-protection-of-the-share-against-stones-digging-de
- adjustable-speed-from-the-control-panel-tape-with-zip-fastening-rubber-friction-drive-for-the-2nd-main-web-haulm-tape-with-a-pitch-of-200-mm-spring-holding-the-haulm-tape-at-the-front
- standard-version-additional-scrappers-in-the-haulm-belt-cooler-for-your-own-hydraulics-1st-separator-tape
- pitch-40-mm-needle-rod-with-v-profile-1-separator-scrapers-1-separator-scrappers-smooth-roller-spiral-roller

s-slip-check-of-the-1st-main-web-and-2nd-separator-h
ydraulic-regulation-of-the-speed-difference-between-
the-needle-tape-and-the-needle-tape-scrapers-

- 5-rollers
- radial-liquid-regulation
- without-tank-pre-cleaning-rollers
- distance-20-mm-stone-container-with-tape-front-elevator-with-ultrasonic-sensor-60t-tank-automatic-tank-filling-regulation-system-with-automation-front-elevator-and-filling-support-broken-tank-tip-potato-fall-shock-absorber-mounted-on-the-tank-filling-pall
- installation-possible-max-8-cameras-reversing-camera
- mounted-with-lighting-camera-of-the-1st-main-web
- mounted-with-lighting-zone-camera-between-1st-and-2nd-separator
- mounted-with-lighting-selection-table-camera
- mounted-with-lighting-upper-tank-segment-camera
- mounted-with-lighting-visual-protect-can-bus-controlled-by-the-monitoring-system-vc-50-terminal-joystick-box-instead-of-the-standard-terminal-multi-function-joystick-instead-of-the-joystick-module-on-the-right-load-sensing-with-control-cable-to-the-tractor
- 5-wakw
- radialna-pynna-regulacja
- bez-zbiornika-waki-do-czyszczenia-wstepnego-odlego-20-mm-zbiornik-na-kamienie-z-tam-elewator-czoowyy-z-czujnikiem-ultradzikowym-60t-zbiornik-ukad-automatyczne-j-regulacji-napeniania-zbiornika-z-automatyk-elewatora-czoowego-i-wspomaganie-napeniania-amana-koc
- moliwo-instalacji-maks-8-kamer-kamera-cofania
- zamontowana-z-owietleniem-kamera-1-tamy-odsiewajcej
- zamontowana-z-owietleniem-kamera-strefy-midzy-1-a-2-separatorem
- zamontowana-z-owietleniem-kamera-stou-selekcyjnego
- zamontowana-z-owietleniem-kamera-segmentu-grnego-zbiornika
- zamontowana-z-owietleniem-visual-protect-can-bus-sterowany-przez-system-monitoringu-terminal-vc-50-joystick-box-zamiast-standardowego-terminala-joystick-wielofunkcyjny-zamiast-moduu-z-joystickami-po-prawej-load-sensing-z-przewodem-sterujcym-do-cignika-