

# FRICKE

## Maszyzny Rolnicze

**FRICKE Maszyzny Rolnicze Sp. z o.o. Mrągowo**  
Ul. Przemysłowa 6  
11-700 Mrągowo  
Tel: +48 783 222 777  
Fax:

### Joskin SIROKO S5013/12V [YD8SRK120NJB05039]

Year of manufacture: 2023

Date: 18.10.2024

Design:

Manure technology + manure technology

Category:

Manure spreader

**175.400,<sup>00</sup> zł**  
plus VAT 23% (215.742,<sup>00</sup> zł Gross)



### Equipment

State	new
Air brake	✓
Loading volume	12,00
Payload	12,00
Technical condition	New
Number of rollers	2
Roller type	stehend

### Description:

- description
- narrow-shell-spreader
- fully-galvanized-box
- sides-in-4-mm-hle-steel
- bolted-floor-in-3-mm-galvanized-steel
- 2-link-chains-14-mm
- switching-of-the-conveyor-with-a-two-wayhydraulic-tractor-distributor
- walterscheid-shaft-with-screw-protection
- gimbal-with-freewheel-mechanism-at-the-rear
- transverse-drawbar-suspension-with-parabolicsprings
- pneumatic-braking-system
- full-led-retractable-signal-lights

- adapter-with-2-vertical-shafts-900-mm-with-shaft-194-mm
- pto-shaft-1000-rpm
- adapter-speed-423-rpm
- steel-hb-450-reversible-teeth-70-x-10-mm-additional-equipment
- european-approval-dmc-10-t-per-axle-3-t-towing-eyelet-at-30-kmh-for-a-single-axle-vehicle-cats
- wheels-65075r32-bkt-agrimax-rt600-172-a8-dt-43-o-1785-x-645-mm-6300-kg-per-wheel-at-40-kmh-instead-of-400r225
- air-brakes-with-sprung-actuator-instead-ofstandard-parking-brake-compulsory-air-brakes
- fixed-axle-mounting-only
- led-side-lights
- rear-hydraulic-slider-bi-directional-for-s501312v-and-s551313v-models
- wide-angle-1-way-shaft-walterscheid
- cam-protection-instead-of-screw-protection-forcardan-shaft
- ferti-control-300-controller-including-electric-control-of-belt-travel-with-flow-regulator-switch-for-switching-the-conveyor-on-and-off-and-reversing-the-direction-of-belt-travel-by-switching-the-hydraulic-switch-in-the-cab-opis
- Narrow shell spreader
- Fully galvanized box
- 4 mm HLE steel siding
- Bolt-on floor made of 3 mm galvanized steel
- 2 link chains Ø 14 mm
- Switching the conveyor with a two-way-hydraulic tractor distributor
- Walterscheid roller with screw protection
- Gimbal with freewheel mechanism at the rear
- Transverse drawbar suspension with parabolic springs
- Pneumatic braking system
- Full LED retractable signal lights
- Adapter with 2 vertical shafts Ø 900 mm with shaft Ø 194 mm
- wa-przekanikowy-1000-obrmin
- prdko-obrotowa-adaptera-423-obrmin
- zby-ze-stali-hb-450-odwracalne-70-x-10-mm-dodatkowe-wyposazenie
- European approval DMC 10 T per axle (+ 3 T towing eyelet) at 30 km/h for single axle vehicle (cat.S)
- Wheels 650/75R32 (BKT) AGRIMAX RT600 172 A8 DT 43 (O 1,785 x 645 mm, 6,300 kg per wheel at 40 km/h) instead of 400R22.5
- hamulce-pneumatyczne-z-siownikiem-resorowanym-z-amiast-standardowego-hamulca-postojowego-obowiazkowe-hamulce-pneumatyczne
- monta-wycznie-na-osi-staej
- LED sidelights

- Rear Hydraulic Gate (bidirectional) for models S5013/12V and S5513/13V
- Wide-angle 1-sided roller (Walterscheid)
- CURVED cam instead of screw-type cardan shaft
- sterownik-ferti-control-300-zawierajcy-elektryczne-sterowanie-przesuwem-tamy-z-regulatorem-przepływu-przeznika-dochodzenia-i-wychodzenia-przeznika-i-odwracania-kierunku-przesuwu-tamy-poprzez-przeznienie-hydraulicznego-wcznika-w-kabinie-