

FRICKE

Maszyny Rolnicze

FRICKE Maszyny Rolnicze Sp. z o.o. Mragowo
Ul. Przemysłowa 6
11-700 Mragowo
Tel: +48 783 222 777
Fax:

Joskin MODULO2 16000 MEB [YD81600TSMJB39892]

Year of manufacture: 2023

Date: 24.11.2024

Design:

Manure technology + manure technology

Category:

Pumpass

188.400,⁰⁰ zł

plus VAT 23% (231.732,⁰⁰ zł Gross)



Equipment

Tyres	710/50R 26.5
State	new
Suspension	mechanical
Filling quantity	16.000,00
Pump capacity	13.000,00

Description:

- Description:
- Slurry tanker MODULO2 16000 MEB, spring drawbar, with vacuum pump
- STEERING AXLE WITH damper (frame) ANDhydraulic lock (two-way)
- ADR axles 150-10G with brakes 420 x 180 mm for vehicles with twin or steering axle instead of 130-10G 406 x 120 mm
- Wheels 710/50R26.5 A 885 (Alliance) 170 D (Ø 1,400 x 732 mm, 8,160 kg per wheel at 40 kph and 4 bar) instead of 400R22.5
- pump-type-pn-130-jurop-13000-lmin-at-atmospheric-pressure

- 540-rpm
- multiplier
- automatic-lubrication-knob-adjustment-cleaning-filter-60-l-hoses-100-mm-and-pressure-valve-joskin-150-mm
- Wide-angle shaft one-sided (Walterscheid)
- ECOPUMP: SPECIAL muffler WITH high CAPACITY and oil recovery, elevated air intake and noise reduction
- longitudinal-indicator-300-x-80-mm-instead-of-indicator-2-position-to-be-determined
- attach-position-drawing-to-order
- per-piece
- Combined level indicator Ø 6" (150 mm) (transparent Plexiglas tube) instead of standard indicator
- Suction valve Ø 6" (150 mm) with movable Perrot jaw
- Rear frame for MODULO2 (equipment preparation)
- Preparation for turbo filler (left side in driving direction)
- Preparation for hydraulic mixer
- preparation-for-jumbo-front-version-200-mm-or-jumbo-side-version-opis
- MODULO2 16000 MEB slurry tanker, sprung drawbar, with vacuum pump
- Trailing axle with shock absorber(rami) and hydraulic lock (bi-directional).
- ADR 150-10G axles with brakes 420 x 180 mm for a vehicle with dual trailing or torsion axles instead of 130-10G 406 x 120 mm
- Wheels 710/50R26.5 A 885 (Alliance) 170 D (Ø 1,400 x 732 mm, 8,160 kg per wheel at 40 km/hr and 4 bar) instead of 400R22.5
- pompa-typu-pn-130-jurop-13000-lmin-przy-cinieniu-atmosferycznym
- 540-obrmin
- multiplikator
- smarowanie-automatyczne-regulacja-pokrtem-filtr-czy-szczycy-60-l-przewody-100-mm-i-zawr-cinieniowy-joskin-150-mm-zamiast-mec-8000
- Wide-angle 1-sided roller (Walterscheid)
- ECOPUMP: large capacity special muffler with oil recovery, raised air intake point and noise reduction
- wskanik-poduny-300-x-80-mm-zamiast-wskanika-2-poenie-do-ustalenia
- do-zamwienia-doczy-rysunek-poenia
- za-szt
- Connected Ø 6" (150 mm) level indicator (transparent plexiglass tube) instead of standard indicator
- Suction valve Ø 6" (150 mm) with movable jaw Perrot
- Rear frame for MODULO2 (preparation for accessories)
- Preparation for the turbo filler (on the left looking in the direction of travel)

- Preparation for the hydraulic mixer
- przygotowanie-do-jumbo-przedniegoniebudowanego-200-mm-lub-do-jumbo-bocznego-