

FRICKE

Maszyny Rolnicze

FRICKE Maszyny Rolnicze Sp. z o.o. Mragowo
Ul. Przemysłowa 6
11-700 Mragowo
Tel: +48 732 106 371
Fax:

Joskin MODULO2 14000 MEB [YD81400TSMJB39915]

Year of manufacture: 2023

Date: 09.03.2025

Design:

Manure technology + manure technology

Category:

Pumpass

177.800,⁰⁰ PLN

plus VAT 23% (218.694,⁰⁰ PLN Gross)



Equipment

State

new

Description:

X

Description:

- Description:
- slurry-tanker-modulo2-14000-meb-sprung-drawbar-with-vacuum-pump
- follow-up-axle-with-shock-absorber-frame-and-hydraulic-lock-bidirectional
- adr-130-10g-axles-with-406-x-120-mm-brakes-for-vehicle-with-twin-follow-up-or-steering-axle-instead-of-100130-8g-400-x-80-mm
- cart-springs-1600-mm
- wheels-65055r265-agriterra-02-mitas-169-d-1389-x-645-mm-7890-kg-per-wheel-at-40-kmh-and-4-bar-instead-of-400r225
- pump-type-pn-106-jurop-11000-lmin-at-atmospheric-

- pressure
- 10000-lmin-at-60-vacuum
- 540-rpm-multiplier
- with-automatic-lubrication
- Wide-angle shaft one-sided (Walterscheid)
- eco
- cleaning-filter-cleaning-filter-with-ecopump-instead-of-cleaning-filter-available-only-with-pumps-max-80-mm
- combined-level-indicator-6-150-mm-plexiglass-tube-instead-of-standard-indicator
- suction-valve-6-150-mm-with-movable-perrot-claw
- rear-frame-for-modulo2-preparation-for-joskin-rear-equipment-including-spigot-8-200-mm-at-the-top-of-the-bottom-for-vacuum-pumps-only-ramp-supports-and-drain-plug-8-200-mm-with-quick-opening
- preparation-for-turbo-filler-on-the-left-side-looking-in-the-driving-direction
- Preparation for hydraulic mixer
- 6-m-hose-015-m-galvanized-pipe-6-perrot-male-coupling-instead-of-4-m-hose-015-m-galvanized-pipe-6-perrot-male-coupling-opis
- MODULO2 14000 MEB slurry tanker, sprung drawbar, with vacuum pump
- Trailing axle with shock absorber(rami) and hydraulic lock (bi-directional).
- ADR 130-10G axles with brakes 406 x 120 mm for a vehicle with dual trailing or torsion axles instead of 100/130-8G 400 x 80 mm
- Cart springs 1,600 mm
- Wheels 650/55R26.5 Agriterra 02 (MITAS) 169 D (Ø 1,389 x 645 mm, 7,890 kg per wheel at 40 km/hr and 4 bar) instead of 400R22.5
- pompa-typu-pn-106-jurop-11000-lmin-przy-cinieniu-atmosferycznym
- 10000-lmin-przy-60-prni
- 540-obrmin-multiplikator
- ze-smarowaniem-automatycznym
- Wide-angle 1-sided roller (Walterscheid)
- eco
- filtr-czyszczycy-filtr-czyszczycy-z-ecopump-zamiast-filtra-czyszczczego-dostpny-wycznie-z-pompami-max-80-mm
- Connected Ø 6" (150 mm) level indicator (transparent plexiglass tube) instead of standard indicator
- Suction valve Ø 6" (150 mm) with movable jaw Perrot
- Rear frame for MODULO2 (preparation for JOSKIN rear attachment) including Ø 8" (200 mm) spigot in the top of the bottom (for vacuum pumps only), ramp supports and Ø 8 (200 mm) drain plug with quick opening
- Preparation for the turbo filler (on the left looking in the direction of travel)

- Preparation for the hydraulic mixer
- 6 m hose + 0.15 m cable galv. Ø 6 Perrot male connector instead of 4 m hose + 0.15 m cable galv. Ø 6 Perrot male connector